

DISCOVER THE 40V BATTERY PRODUCT RANGE

We have expanded our EfcO 40V battery line with four new solutions designed for those seeking efficiency and versatility: the PTi 35 pruner, the DSi 35 HL shaft hedge trimmer, the DSi 35 brushcutter, and the multifunctional DSi 35 D brushcutter.

These tools are designed for private users who need to perform **medium-intensity tasks**, even more demanding than those manageable with other products in the range. With a brushless motor positioned next to the battery and a **mechanical transmission equivalent to that of petrol-powered machines**, these models feature an innovative configuration that offers **high performance** combined with **robustness and reliability**. Moreover, thanks to vector control electronics, energy losses are minimized, significantly improving usage autonomy. In addition, the entire 40V range features **Constant Power technology** — an advanced electronic system that guarantees consistent performance until the battery is fully drained.

With this integration, we have enriched the 40V line offering with even more efficient products, designed to expand possible applications and meet increasingly specific needs.

Explore all the models!



The new products

With the introduction of the **new models**, our 40V battery-powered range takes a step forward in terms of ergonomics and performance. The brushless motor, positioned close to the battery, ensures **perfect balance during use**.

These tools are **ideal for gardening enthusiasts** tackling medium-complexity tasks, and they stand out for their ability to handle more demanding jobs compared to other machines in the same category. Moreover, they represent a tangible evolution of the range: **enhancing power and operational durability while expanding usage options** and the environments in which they can be employed.



Chainsaws and pruners

For cutting firewood or small to medium diameter branches, **battery-powered chainsaws and pruners** offer a practical option without the hassle of a cord.

The **MTi 30 model** stands out for its compact structure and design focused on maneuverability, ensuring greater comfort during use.

The **PTi 35 pruner**, on the other hand, is designed to reach branches over 2.5 meters high, making pruning at height easier. Besides power, it combines effective cutting with all the advantages of battery technology: lightweight construction, quiet operation, and zero emissions.



Hedge trimmers

To take care of hedges and greenery around the home, the **TGi 45 and DSi 35 HL battery-powered hedge trimmers** are the perfect choice.

Equipped with **high-quality blades**, finished with **laser treatment** to ensure clean and gentle cuts on vegetation, they combine **ease of handling and user comfort with zero emissions**, making them a **sustainable and effective solution**.



Brushcutters

In everyday gardening work, the **DSi 30, DSi 35, and the multifunctional DSi 35 D brushcutters** prove to be practical and versatile allies. They combine the lightness and simplicity typical of battery-powered tools with the practicality of the **Load&Go head**, ensuring quick and hassle-free use. The **DSi 35 D multifunctional model** is particularly suitable for home garden maintenance and helps you save space: thanks to a single engine and multiple attachments, it can be used as a **pruner, hedge trimmer, and brushcutter**.



Lawnmowers

Our range of **battery-powered lawnmowers** — including the **LRI 40 P**, **LRI 44 P**, **LRI 44 T**, **LRI 48 P**, and **LRI 48 T** models — offers a quiet, precise, and easy-to-manage mowing experience. The **LRI 44** and **LRI 48** machines feature a **dual battery compartment**, allowing two 5 Ah batteries to be used simultaneously for extended runtime on larger areas without interruptions. Thanks to their **sturdy steel structure**, these products are built to last and come equipped with **centralized cutting height adjustment** and a **large grass collection bag**. By choosing the **LRI 48** model, you'll also benefit from the practical **4-in-1 cutting function**, which lets you choose between grass collection, mulching, or side discharge. For smaller spaces, the **LRI 40 P**, built with a **lightweight plastic deck**, is the most agile and easy-to-handle option.



Blowers

Today, the **leaf blower** has become an essential tool for keeping gardens and outdoor areas tidy, and the **SAI 60 BOOST** model stands out as one of the most advanced solutions in its category. Thanks to its **battery-powered operation**, **power calibrated for all cleaning needs**, and the **adjustable airspeed control**, it offers **convenience**, **efficiency**, and **maximum freedom of movement** during use.

The new products

With the introduction of the **new models**, our 40V battery-powered range takes a step forward in terms of ergonomics and performance. The brushless motor, positioned close to the battery, ensures **perfect balance during use**.

These tools are **ideal for gardening enthusiasts** tackling medium-complexity tasks, and they stand out for their ability to handle more demanding jobs compared to other machines in the same category. Moreover, they represent a tangible evolution of the range: **enhancing power and operational durability while expanding usage options** and the environments in which they can be employed.



Plus point



Weight well distributed

The brushless motor, positioned close to the battery, ensures balanced weight distribution for working with greater control.




Maximum visibility

Thanks to the small size of the cutting unit, you always have a clear view of the work area and greater precision in your movements.



Head always ready





Need to change the line? With the 103 mm Load&Go Compact head, it only takes a moment: in just 20 seconds you are ready to get back to work, without interruptions.



Adjustable blades

The steel blades tilt from 0° to 180° in 12 positions, to easily adapt to the shape of the hedge and ensure a precise cut.

Technical data

| Model |  PTI 35 |  DSI 35 |  DSI 35 HL |  DSI 35 D - Kit with 3 applications, Bi 5,0 EF battery and CRG charger |
|---|--|--|--|--|
| Bar length | 10", 25 cm | - | - | - |
| Chain (pitch x gauge) | 3/8"x.050" | - | - | 3/8"x.050", pruner application |
| Runtime up to | 2.0 Ah: 45 cuts light use, 2.0 Ah: 30 cuts intensive use, 5.0 Ah: 115 cuts light use, 5.0 Ah: 75 cuts intensive use | 2.0 Ah: 15' light use, 2.0 Ah: 10' intensive use, 5.0 Ah: 38' light use, 5.0 Ah: 25' intensive use | 5.0 Ah: 50' intensive use, 2.0 Ah: 20' intensive use, 5.0 Ah: 67' light use, 2.0 Ah: 27' light use | - |
| Motor type | Brushless | Brushless | Brushless | Brushless |
| Sound pressure/power level | 88.8/99 dB(A) | 81.8 / 89.53 dB(A) | 86.6/93.54 dB(A) | - |
| Voltage | 40 V | 40 V | 40 V | 40 V |
| Lh/rh vibration level | 4.2/3.4 m/s ² | < 2.5 m/s ² | 4.0/2.5 m/s ² | - |
| Compatible batteries | Bi 2,0 EF, Bi 5,0 EF | Bi 2,0 EF, Bi 5,0 EF | Bi 2,0 EF, Bi 5,0 EF | Bi 2,0 EF, Bi 5,0 EF |
| Bar type | sprocket | - | - | - |
| Oil reservoir capacity | 0.13 L | - | - | - |
| Charging time with CRG | 88' (2.0 Ah), 220' (5.0 Ah) | 88' (2.0 Ah), 220' (5.0 Ah) | 88' (2.0 Ah), 220' (5.0 Ah) | 88' (2.0 Ah), 220' (5.0 Ah) |
| Charging time with FAST CRG | 40' (2.0 Ah), 90' (5.0 Ah) | 40' (2.0 Ah), 90' (5.0 Ah) | 40' (2.0 Ah), 90' (5.0 Ah) | 40' (2.0 Ah), 90' (5.0 Ah) |
| Overall length of machine | 2.10 m | - | 2.35 cm | - |
| Cutting performance | cut of wood section up to 10 cm diameter. Working time can be subject to variations according to working conditions and type of wood to be cut | indicative data which may vary depending on working conditions and the type of vegetation cut | indicative data which may vary depending on working conditions and the type of vegetation cut | indicative data which may vary depending on working conditions and the type of vegetation cut |
| Dry weight without battery, bar and chain | 4.1 kg | - | - | - |
| Cutting components | - | 103 mm dia. Load&Go Compact line head with 2.4 mm line | - | 103 mm dia. Load&Go Compact line head with 2.4 mm line |
| Cutting diameter | - | 30 cm | - | - |
| Grip | - | single | - | single |
| Tube diameter | - | 26 mm | - | 26 mm |
| Weight without cutting tools and battery | - | 4.2 kg | - | - |
| Blade type | - | - | double blade, rotatable through 12 positions from 0° to 180° | double blade, rotatable through 12 positions from 0° to 180°, hedgetrimmer application |
| Blade length | - | - | 400 mm | 400 mm, hedgetrimmer application |
| Blade pitch | - | - | 30 mm | 30 mm, hedgetrimmer application |
| Weight without battery | - | - | 5.6 kg | - |
| Bar length (nose) | - | - | - | 25 cm, 10", pruner application |
| Weight of engine unit | - | - | - | 2.9 kg |

Chainsaws and pruners

For cutting firewood or small to medium diameter branches, **battery-powered chainsaws and pruners** offer a practical option without the hassle of a cord. The **MTi 30** model stands out for its compact structure and design focused on maneuverability, ensuring greater comfort during use.

The **PTi 35** pruner, on the other hand, is designed to reach branches over 2.5 meters high, making pruning at height easier. Besides power, it combines effective cutting with all the advantages of battery technology: lightweight construction, quiet operation, and zero emissions.



Plus point



Low weight

Thanks to its compact design and low weight, this machine is easy to manoeuvre, allowing you to work for a long time without fatigue.



Weight well distributed

The brushless motor, positioned close to the battery, ensures balanced weight distribution for working with greater control.



Quick adjustment

Adjusting the chain is done quickly and without the use of tools, allowing you to get the right tension in just a few steps.



Reinforced shaft

The rigid 8 mm drive shaft supported by six self-lubricating bushings gives you solidity and ensures reliable operation over time.

Technical data

| Model |  PTi 35 |  MTi 30 |
|---|--|--|
| Bar length | 10", 25 cm | 12", 30 cm |
| Chain (pitch x gauge) | 3/8" x .050" | 3/8" x .043" |
| Runtime up to | 2.0 Ah: 45 cuts light use, 2.0 Ah: 30 cuts intensive use, 5.0 Ah: 115 cuts light use, 5.0 Ah: 75 cuts intensive use | 5.0 Ah: 160 cuts |
| Motor type | Brushless | Brushless |
| Sound pressure/power level | 88.8/99 dB(A) | - |
| Voltage | 40 V | 40 V |
| Lh/rh vibration level | 4.2/3.4 m/s ² | - |
| Compatible batteries | Bi 2,0 EF, Bi 5,0 EF | Bi 5,0 EF |
| Bar type | sprocket | Oregon, sprocket-nose |
| Oil reservoir capacity | 0.13 L | 0.2 L |
| Charging time with CRG | 88' (2.0 Ah), 220' (5.0 Ah) | 220' (5.0 Ah) |
| Charging time with FAST CRG | 40' (2.0 Ah), 90' (5.0 Ah) | 90' (5.0 Ah) |
| Overall length of machine | 2.10 m | - |
| Cutting performance | cut of wood section up to 10 cm diameter. Working time can be subject to variations according to working conditions and type of wood to be cut | cut of wood section up to 10 cm diameter. Working time can be subject to variations according to working conditions and type of wood to be cut |
| Dry weight without battery, bar and chain | 4.1 kg | 2.8 kg |
| Chain speed | - | 16 m/s |
| Oil Pump | - | automatic, zero oil flow with engine stopped |
| Chain tensioner | - | tool-free, knob system |


Hedgetrimmers

To take care of hedges and greenery around the home, the TGi 45 and DSi 35 HL battery-powered hedge trimmers are the perfect choice.

Equipped with **high-quality blades**, finished with **laser treatment** to ensure clean and gentle cuts on vegetation, they combine **ease of handling** and **user comfort** with **zero emissions**, making them a **sustainable and effective** solution.



Plus point



Double blades

High quality and laser cut to give you a workmanlike result and not to damage the plants.



Maximum visibility

Thanks to the small size of the cutting unit, you always have a clear view of the work area and greater precision in your movements.



Battery Bi 2,0 EF

Long-lasting, consistent power thanks to lithium-ion technology. It is interchangeable with the 5 Ah battery.



Built-in support

The machine is equipped with a support to be fixed to the base, so using it will be even more comfortable and practical.

Technical data

| Model |  TGi 45 |  DSi 35 HL |
|-----------------------------|---|--|
| Blade type | double | double blade, rotatable through 12 positions from 0° to 180° |
| Blade length | 450 mm | 400 mm |
| Runtime up to | 2.0 Ah: 48' light use, 2.0 Ah: 36' intensive use, 5.0 Ah: 120' light use, 5.0 Ah: 90' intensive use | 5.0 Ah: 50' intensive use, 2.0 Ah: 20' intensive use, 5.0 Ah: 67' light use, 2.0 Ah: 27' light use |
| Voltage | 40 V | 40 V |
| Charging time with CRG | 88' (2.0 Ah), 220' (5.0 Ah) | 88' (2.0 Ah), 220' (5.0 Ah) |
| Charging time with FAST CRG | 40' (2.0 Ah), 90' (5.0 Ah) | 40' (2.0 Ah), 90' (5.0 Ah) |
| Compatible batteries | Bi 2,0 EF, Bi 5,0 EF | Bi 2,0 EF, Bi 5,0 EF |
| Motor type | Brushed | Brushless |
| Blade pitch | 20 mm | 30 mm |
| Sound pressure/power level | 81.4/90 dB(A) | 86.6/93.54 dB(A) |
| Lh/rh vibration level | < 2.5 m/s ² | 4.0/2.5 m/s ² |
| Cutting performance | indicative data which may vary depending on working conditions and the type of vegetation cut | indicative data which may vary depending on working conditions and the type of vegetation cut |
| Weight without battery | 3.0 kg | 5.6 kg |
| Overall length of machine | - | 2.35 cm |

Brushcutters

In everyday gardening work, the DSi 30, DSi 35, and the multifunctional DSi 35 D brushcutters prove to be practical and versatile allies. They combine the lightness and simplicity typical of battery-powered tools with the practicality of the Load&Go head, ensuring quick and hassle-free use. The DSi 35 D multifunctional model is particularly suitable for home garden maintenance and helps you save space: thanks to a single engine and multiple attachments, it can be used as a pruner, hedge trimmer, and brushcutter.



Plus point



Practical

With the adjustable loop front handle, it is definitely a handy brushcutter.



Well distributed weight

The brushless motor, positioned close to the battery, ensures balanced weight distribution for working with greater control.



Quick and precise cutting




The cutting system reaches up to 6000 rpm, with gradual regulation via accelerator: so you work with precision, at your own pace.



Battery Bi 2.0 EF

The lithium-ion battery gives you maximum performance. The brushcutter also mounts the 5 Ah battery.

Technical data

| Model |  DSi 30 |  DSi 35 |  DSi 35 D - Kit with 3 applications, Bi 5,0 EF battery and CRG charger |
|--|--|--|--|
| Cutting components | 103 mm dia. Load&Go line head with 2 mm dia. nylon line | 103 mm dia. Load&Go Compact line head with 2.4 mm line | 103 mm dia. Load&Go Compact line head with 2.4 mm line |
| Runtime up to | 2.0 Ah: 16' intensive use, 2.0 Ah: 24' light use, 5.0 Ah: 60' light use, 5.0 Ah: 40' intensive use | 2.0 Ah: 15' light use, 2.0 Ah: 10' intensive use, 5.0 Ah: 38' light use, 5.0 Ah: 25' intensive use | - |
| Motor type | Brushed | Brushless | Brushless |
| Cutting diameter | 30 cm | 30 cm | - |
| Grip | single, adjustable | single | single |
| Voltage | 40 V | 40 V | 40 V |
| Compatible batteries | Bi 2,0 EF, Bi 5,0 EF | Bi 2,0 EF, Bi 5,0 EF | Bi 2,0 EF, Bi 5,0 EF |
| Charging time with CRG | 88' (2.0 Ah), 220' (5.0 Ah) | 88' (2.0 Ah), 220' (5.0 Ah) | 88' (2.0 Ah), 220' (5.0 Ah) |
| Charging time with FAST CRG | 40' (2.0 Ah), 90' (5.0 Ah) | 40' (2.0 Ah), 90' (5.0 Ah) | 40' (2.0 Ah), 90' (5.0 Ah) |
| Sound pressure/power level | 76/87 dB(A) | 81.8 / 89.53 dB(A) | - |
| Lh/rh vibration level | < 2.5 m/s ² | < 2.5 m/s ² | - |
| Cutting performance | indicative data which may vary depending on working conditions and the type of vegetation cut | indicative data which may vary depending on working conditions and the type of vegetation cut | indicative data which may vary depending on working conditions and the type of vegetation cut |
| Weight without battery | 2.9 kg | - | - |
| Tube diameter | - | 26 mm | 26 mm |
| Weight without cutting tools and battery | - | 4.2 kg | - |
| Bar length (nose) | - | - | 25 cm, 10", pruner application |
| Chain (pitch x gauge) | - | - | 3/8"x.050", pruner application |
| Blade type | - | - | double blade, rotatable through 12 positions from 0° to 180°, hedgetrimmer application |
| Blade length | - | - | 400 mm, hedgetrimmer application |
| Blade pitch | - | - | 30 mm, hedgetrimmer application |
| Weight of engine unit | - | - | 2.9 kg |

Lawnmowers

Our range of **battery-powered lawnmowers** — including the **LRI 40 P**, **LRI 44 P**, **LRI 44 T**, **LRI 48 P**, and **LRI 48 T** models — offers a quiet, precise, and easy-to-manage mowing experience.

The **LRI 44** and **LRI 48** machines feature a **dual battery compartment**, allowing two 5 Ah batteries to be used simultaneously for extended runtime on larger areas without interruptions.

Thanks to their **sturdy steel structure**, these products are built to last and come equipped with **centralized cutting height adjustment** and a **large grass collection bag**.

By choosing the **LRI 48** model, you'll also benefit from the practical **4-in-1 cutting function**, which lets you choose between grass collection, mulching, or side discharge.

For smaller spaces, the **LRI 40 P**, built with a **lightweight plastic deck**, is the most agile and easy-to-handle option.



Plus point



Guaranteed constant power

With the double 5 Ah battery bay, you double your working time.



4-cutting device

Charged batteries with low power consumption. Fix it to the wall: it is within reach without taking up space.



Intuitive controls






And accessible. For example, you can adjust the cutting height of the grass from 28 to 75 mm.



CRG Battery Charger

Charged batteries with low power consumption. Fix it to the wall: it is within reach without taking up space.

Technical data

| Model |  LRI 40 P |  LRI 44 P |  LRI 44 T |  LRI 48 P |  LRI 48 T |
|-----------------------------|--|--|--|--|--|
| Deck | polypropylene | steel | steel | steel | steel |
| Cutting width | 37 cm | 41 cm | 41 cm | 46 cm | 46 cm |
| Runtime up to | 120 m ² (1×2.0 Ah), 300 m ² (1×5.0 Ah) | 140 m ² (1×2.0 Ah), 280 m ² (2×2.0 Ah), 350 m ² (1×5.0 Ah), 700 m ² (2×5.0 Ah) | 250 m ² (1×5.0 Ah), 500 m ² (2×5.0 Ah) | 250 m ² (1×5.0 Ah), 500 m ² (2×5.0 Ah) | 250 m ² (1×5.0 Ah), 500 m ² (2×5.0 Ah) |
| Propulsion | push-type | push-type | self-propelled | push-type | self-propelled |
| | 1 | up to 2 | up to 2 | up to 2 | up to 2 |
| Compatible batteries | Bi 2,0 EF, Bi 5,0 EF | Bi 2,0 EF, Bi 5,0 EF | Bi 5,0 EF | Bi 5,0 EF | Bi 5,0 EF |
| Motor type | Brushless | Brushless | Brushless | Brushless | Brushless |
| Voltage | 40 V | 40 V | 40 V | 40 V | 40 V |
| Power | up to 750 W | up to 750 W | up to 750 W | - | - |
| Cutting adjustment | central | central | central | central | central |
| Cutting height | from 18 to 60 mm | from 28 to 75 mm | from 28 to 75 mm | from 28 to 75 mm | from 28 to 75 mm |
| Grass box capacity | 40 L | 70 L | 70 L | 70 L | 70 L |
| Sound pressure/power level | 80.7/96 dB(A) | 76.3/89 dB(A) | 76.3/89 dB(A) | 76.3/89 dB(A) | 76.3/89 dB(A) |
| Lh/rh vibration level | < 2.5 m/s ² | < 2.5 m/s ² | < 2.5 m/s ² | < 2.5 m/s ² | < 2.5 m/s ² |
| Plus | < 300 m ² | < 700 m ² | < 500 m ² | < 500 m ² | < 500 m ² |
| Mulching/Side discharge | not available/not available | not available/not available | not available/not available | standard/standard | standard/standard |
| Charging time with CRG | 88' (2.0 Ah), 220' (5.0 Ah) | 88' (2.0 Ah), 220' (5.0 Ah) | 220' (5.0 Ah) | 220' (5.0 Ah) | 220' (5.0 Ah) |
| Charging time with FAST CRG | 40' (2.0 Ah), 90' (5.0 Ah) | 40' (2.0 Ah), 90' (5.0 Ah) | 90' (5.0 Ah) | 90' (5.0 Ah) | 90' (5.0 Ah) |
| Cutting performance | cutting performance depends on several factors including: garden shape, surface characteristics (length, grass moisture), ground speed, type of cut (collection, mulching or side discharge) | cutting performance depends on several factors including: garden shape, surface characteristics (length, grass moisture), ground speed, type of cut (collection, mulching or side discharge) | cutting performance depends on several factors including: garden shape, surface characteristics (length, grass moisture), ground speed, type of cut (collection, mulching or side discharge) | cutting performance depends on several factors including: garden shape, surface characteristics (length, grass moisture), ground speed, type of cut (collection, mulching or side discharge) | cutting performance depends on several factors including: garden shape, surface characteristics (length, grass moisture), ground speed, type of cut (collection, mulching or side discharge) |
| Weight without battery | 13.0 kg | 23.0 Kg | 25.0 kg | 27.0 kg | 29.0 kg |

Blowers

Today, the leaf blower has become an essential tool for keeping gardens and outdoor areas tidy, and the SAI 60 BOOST model stands out as one of the most advanced solutions in its category.

Thanks to its battery-powered operation, power calibrated for all cleaning needs, and the adjustable airspeed control, it offers convenience, efficiency, and maximum freedom of movement during use.



Plus point



Extra energy

Are you dealing with stubborn leaves or heavy residue? Activate BOOST mode and increase airflow for an even firmer boost.



Maximum balance


It will feel lighter: the well-balanced center of gravity helps you work longer, without straining your wrist.



Convenient storage


The hose separates with a simple click thanks to the integrated button: it is perfect if you have little space to store the machine or if you need to transport it.

Technical data

| | |
|-----------------------------|--|
| Model |  SAI 60 BOOST |
| Max air speed | 40 m/s (BOOST 50 m/s) |
| Runtime up to | 2.0 Ah: 12' maximum speed, 2.0 Ah: 32' minimum speed, 5.0 Ah: 25' maximum speed, 5.0 Ah: 82' minimum speed |
| Motor type | Brushless |
| Voltage | 40 V |
| Adjustable air velocity | yes, specific command (roller) |
| Sound pressure/power level | 88,6/98 dB(A) |
| Lh/rh vibration level | < 2.5 m/s ² |
| Charging time with CRG | 88' (2.0 Ah), 220' (5.0 Ah) |
| Compatible batteries | Bi 2,0 EF, Bi 5,0 EF |
| Charging time with FAST CRG | 40' (2.0 Ah), 90' (5.0 Ah) |
| Use | Home Plus |
| Weight without battery | 2.8 kg |



Chain sharpener bars

For perfect sharpening of chain cutter teeth

| | | Code | | | | | | | | | | | | | |
|---|------------|-----------|--------|----------|--------|--------|--------|--------------|----------|----------|--------|-----------|----------|----------|---|
|  | Round bars | 001000605 | - | - | - | - | X | - | - | - | - | - | - | - | - |
| | | | PTi 35 | LRI 40 P | DSi 30 | TCi 45 | MTi 30 | SAi 60 BOOST | LRI 44 P | LRI 44 T | DSi 35 | DSi 35 HL | LRI 48 P | LRI 48 T | DSi 35 D - Kit with 3 applications, Bi 5,0 EF battery and CRG charger |





Batteries

Rugged, shockproof and high performance


| | | Code | | | | | | | | | | | | | |
|---|-------------------|-----------|--------|----------|--------|--------|--------|--------------|----------|----------|--------|-----------|----------|----------|---|
|  | Bi 5,0 EF battery | 54030004C | X | X | X | X | X | X | X | X | X | X | X | X | X |
|  | Bi 2,0 EF battery | 54030028 | X | X | X | X | - | X | X | - | X | X | - | - | X |
| | | | PTi 35 | LRI 40 P | DSi 30 | TCi 45 | MTi 30 | SAi 60 BOOST | LRI 44 P | LRI 44 T | DSi 35 | DSi 35 HL | LRI 48 P | LRI 48 T | DSi 35 D - Kit with 3 applications, Bi 5,0 EF battery and CRG charger |

Harness


For the maximum freedom of the operator

| | | Code | PTI 35 | LRI 40 P | DSi 30 | TGI 45 | MTI 30 | SAI 60 BOOST | LRI 44 P | LRI 44 T | DSi 35 | DSi 35 HL | LRI 48 P | LRI 48 T | DSi 35 D - Kit with 3 applications, BI 5,0 EF battery and CRG charger |
|---|---|------------------|--------|----------|--------|--------|--------|--------------|----------|----------|--------|-----------|----------|----------|---|
|  | <p>Harness with cushion</p> | <p>4179164R</p> | - | - | X | - | - | - | - | - | - | - | - | - | - |
|  | <p>Harness with comfort cushion</p> | <p>4179172R</p> | - | - | X | - | - | - | - | - | - | - | - | - | - |
|  | <p>Single harness with snap hook</p> | <p>4160463AR</p> | - | - | X | - | - | - | - | - | - | - | - | - | - |
|  | <p>Single harness without snap hook</p> | <p>60010143R</p> | - | - | X | - | - | - | - | - | - | - | - | - | - |

Guards


| | | | | | | | | | | | | | | | |
|---|---|------------------|---------------|-----------------|---------------|---------------|---------------|---------------------|-----------------|-----------------|---------------|------------------|-----------------|-----------------|--|
| | | | | | | | | | | | | | | | |
|  | <p>Plastic guard for DSi battery-powered brushcutters</p> | <p>54042007R</p> | <p>-</p> | <p>-</p> | <p>X</p> | <p>-</p> | <p>-</p> | <p>-</p> | <p>-</p> | <p>-</p> | <p>-</p> | <p>-</p> | <p>-</p> | <p>-</p> | <p>DSi 35 D - Kit with 3 applications, Bi 5,0 EF battery and CRG charger</p> |
| | | | <p>PTi 35</p> | <p>LRI 40 P</p> | <p>DSi 30</p> | <p>TGi 45</p> | <p>MTi 30</p> | <p>SAi 60 BOOST</p> | <p>LRI 44 P</p> | <p>LRI 44 T</p> | <p>DSi 35</p> | <p>DSi 35 HL</p> | <p>LRI 48 P</p> | <p>LRI 48 T</p> | |

Line heads

| | | | | | | | | | | | | | | | | |
|---|----------------------------------|-----------------|---------------|-----------------|---------------|---------------|---------------|---------------------|-----------------|-----------------|---------------|------------------|-----------------|-----------------|----------|--|
| | | <p>Code</p> | | | | | | | | | | | | | | |
|  | <p>Load&Go head Ø 103 mm</p> | <p>63149002</p> | <p>-</p> | <p>-</p> | <p>X</p> | <p>-</p> | <p>-</p> | <p>-</p> | <p>-</p> | <p>-</p> | <p>-</p> | <p>-</p> | <p>-</p> | <p>-</p> | <p>-</p> | <p>DSi 35 D - Kit with 3 applications, Bi 5,0 EF battery and CRG charger</p> |
| | | | <p>PTi 35</p> | <p>LRI 40 P</p> | <p>DSi 30</p> | <p>TGi 45</p> | <p>MTi 30</p> | <p>SAi 60 BOOST</p> | <p>LRI 44 P</p> | <p>LRI 44 T</p> | <p>DSi 35</p> | <p>DSi 35 HL</p> | <p>LRI 48 P</p> | <p>LRI 48 T</p> | | |

Bar cover

For the ultimate operator safety

| | | | | | | | | | | | | | | | |
|---|------------------|----------------|---------------|-----------------|---------------|---------------|---------------|---------------------|-----------------|-----------------|---------------|------------------|-----------------|-----------------|--|
|  | <p>Bar cover</p> | <p>1144033</p> | <p>-</p> | <p>-</p> | <p>-</p> | <p>-</p> | <p>×</p> | <p>-</p> | <p>-</p> | <p>-</p> | <p>-</p> | <p>-</p> | <p>-</p> | <p>-</p> | <p>-</p> |
| <p>Code</p> | | | <p>PTi 35</p> | <p>LRI 40 P</p> | <p>DSi 30</p> | <p>TCi 45</p> | <p>MTi 30</p> | <p>SAI 60 BOOST</p> | <p>LRI 44 P</p> | <p>LRI 44 T</p> | <p>DSi 35</p> | <p>DSi 35 HL</p> | <p>LRI 48 P</p> | <p>LRI 48 T</p> | <p>DSi 35 D - Kit with 3 applications, BI 5,0 EF battery and CRG charger</p> |