

DISCOVER THE EFCO TRACTOR RANGE

EFCO TRACTOR RANGE

The tractor is the fundamental helper for the care of large gardens, parks and public green areas. In these cases, having an agile and powerful vehicle can make the difference.

Efco tractors are **robust and extremely easy to handle**, equipped with **agile steering systems** that allow you to make even very tight turns. The ease of maneuvering near plants and shrubs allows for greater precision and speed in finishing.

They are also able to **adapt their movement based on the type of terrain**. Equipped with **hydrostatic transmission** which allows you to manage the speed by operating a pedal, without the need to stop or with **mechanical lever transmission**.

The different types of engine, **single-cylinder or twin-cylinder**, offer different **powers based on the models**, so as to always make them suitable for the extension and type of surface you intend to cut.



Frame the QR code and find out more about www.myeefco.com



Rider

Designed for small and medium surfaces, **up to 4,000 m²**. Compact and easy to handle (they have the engine in the rear position) they allow you to move easily and precisely in gardens with plants or in the presence of obstacles.



Side discharge

Ideal for surfaces of **up to 8,000 m²**, they are characterized by greater construction simplicity as they do not collect grass but simply cut it or chop it using the mulching function.



Rear discharge

They allow you to collect grass using large collection baskets; having cutting widths of up to 125 cm and also being powered by twin-cylinder engines, they can be used on gardens of **up to 9,000 m²**.



Professional all-terrain

Designed for cleaning uncultivated areas with dense vegetation, rough or sloping terrain when grass collection is not necessary. Also available with 4x4 transmission, they can easily cover surfaces of **up to 10,000 m²**.

Rider

Designed for small and medium surfaces, **up to 4,000 m²**. Compact and easy to handle (they have the engine in the rear position) they allow you to move easily and precisely in gardens with plants or in the presence of obstacles.



Plus point



Vertical storage

Save space! You can store the ride-on mower in a vertical position during the storage period.



Electromagnetic clutch

The engagement of the electromagnetic clutch occurs quickly and silently with a simple touch of a convenient button on the control panel.



Telescopic lever for emptying the bag

The telescopic lever is easily reachable from the driver's seat. It allows you to tilt and empty the full bag without any muscular effort and without having to twist your torso.



Lever for cutting height adjustment

The adjustment lever is comfortable and easy to reach, with a graduated scale that lets you see immediately the desired cutting height.

Technical data

Model	 ZEPHYR 72/12,5 K H	 ZEPHYR 72/13 H
Turning radius	45 cm	45 cm
Bag capacity	180 L	180 L
Engine make/model	Emak K 1250 AVD	B&S Powerbuilt 3125E AVS series
Cutting height	30-80 mm, 7 positions	30-80 mm, 7 positions
Mulching/Side discharge	optional/optional	standard/standard
Overall dimensions	198x73x110 cm	198x73x110 cm
Number of blades	1	1
Propulsion	hydrostatic	hydrostatic
Displacement	413 cm ³	344 cm ³
Weight	192 kg	192 kg
Plus	< 4000 m ² , 3 cutting device, Deck wash	< 4000 m ² , 4 cutting device, Deck wash
Speed (km/h)	from 0 to 8.6 km/h in forward drive - from 0 to 3.2 km/h in reverse	from 0 to 8.6 km/h in forward drive - from 0 to 3.2 km/h in reverse
Cutting width	72 cm	72 cm

Side discharge

Ideal for surfaces of **up to 8,000 m²**, they are characterized by greater construction simplicity as they do not collect grass but simply cut it or chop it using the mulching function.



Plus point



Lever for cutting height adjustment

Our handy lever for adjusting the cutting height is within easy reach and equipped with a graduated scale. This feature allows you to immediately see the desired height level, with 7 positions available to achieve the perfect cut.



Electromagnetic clutch

The electromagnetic clutch engages quickly and quietly, thanks to a convenient button located on the control panel.



Quick connector "Deck Wash System"



The quick connector "Deck Wash System", located directly on the mowing deck, allows directing water inside to facilitate cleaning of the mowing apparatus.



Front bumper

The large steel front bumper provides robustness and solidity, protecting your ride-on mower from accidental impacts.

Technical data

Model	 EF 99 L/12,5 K M	 EF 99 L/14,5 K	 EF 109 L/16 K
Turning radius	45 cm	45 cm	45 cm
Engine make/model	Emak K 1250 AVD	Emak K 1450 AVD	Emak K 1600 AVD
Overall dimensions	172x129x110 cm	172x129x110 cm	172x139x110 cm
Weight	169 kg	169 kg	170 kg
Cutting height	30-90 mm, 7 positions	30-90 mm, 7 positions	30-90 mm, 7 positions
Plus	< 6000 m ² , Deck wash	< 6000 m ² , Deck wash	< 8000 m ² , Deck wash
Mulching/Side discharge	standard/standard	standard/standard	standard/standard
Speed (km/h)	from 1.6 to 8.3 km/h in forward drive - 2.5 km/h in reverse	from 0 to 8.8 km/h in forward drive - from 0 to 4.5 km/h in reverse	from 0 to 8.8 km/h in forward drive - from 0 to 4.5 km/h in reverse
Propulsion	hydrostatic	hydrostatic	hydrostatic
Displacement	413 cm ³	432 cm ³	452 cm ³
Number of blades	2	2	2
Cutting width	98 cm	98 cm	108 cm

Rear discharge

They allow you to collect grass using large collection baskets; having cutting widths of up to 125 cm and also being powered by twin-cylinder engines, they can be used on gardens of **up to 9,000 m²**.



Technical data




Model	 EF 86 R/12,5 K M	 EF 86 R/14,5 K	 EF 92 R/16 K	 EF 95/16 K	 EF 102 R/16 K	 EF 105/16 K	 EF 125/22 V
Turning radius	45 cm	45 cm	45 cm	75 cm	45 cm	75 cm	70 cm
Engine make/model	Emak K 1250 AVD	Emak K 1450 AVD	Emak K 1600 AVD	Emak K 1600 AVD	Emak K 1600 AVD	Emak K 1600 AVD	B&S V-Twin Intek 7220 OHV series
Overall dimensions	250x96x110 cm	250x96x110 cm	250x99x110 cm	251x117x100 cm	250x109x110 cm	251x117x100 cm	251x119x130 cm
Weight	190 kg	190 kg	192 kg	230 kg	194 kg	240 kg	275 kg
Bag capacity	300 L	300 L	300 L	310 L	300 L	310 L	310 L
Cutting height	30-90 mm, 7 positions	30-90 mm, 7 positions	30-90 mm, 7 positions	20-80 mm, 6 positions	30-90 mm, 7 positions	30-90 mm, 7 positions	30-90 mm, 7 positions
Plus	< 4000 m², Deck wash	< 4000 m², Deck wash	< 4000 m², Deck wash	< 4000 m²	< 7000 m², Deck wash	< 7000 m²	< 9000 m²
Mulching/Side discharge	standard/not available	standard/not available	standard/not available	standard/not available	standard/not available	standard/not available	standard/not available
Speed (km/h)	from 1.6 to 7.5 km/h in forward drive - 2.5 km/h in reverse	from 0 to 8.8 km/h in forward drive - from 0 to 4.5 km/h in reverse	from 0 to 8.8 km/h in forward drive - from 0 to 4.5 km/h in reverse	from 0 to 9.0 km/h in forward drive - from 0 to 4.0 km/h in reverse	from 0 to 8.8 km/h in forward drive - from 0 to 4.5 km/h in reverse	from 0 to 9.0 km/h in forward drive - from 0 to 4.0 km/h in reverse	from 0 to 9.0 km/h in forward drive - from 0 to 4.0 km/h in reverse
Propulsion	5 forward speeds + 1 reverse	hydrostatic	hydrostatic	hydrostatic	hydrostatic	hydrostatic	hydrostatic
Displacement	413 cm³	432 cm³	452 cm³	452 cm³	452 cm³	452 cm³	656 cm³
Number of blades	2	2	2	2	2	2	2
Cutting width	86 cm	86 cm	92 cm	95 cm	102 cm	105 cm	125 cm

Professional all-terrain

Designed for cleaning uncultivated areas with dense vegetation, rough or sloping terrain when grass collection is not necessary. Also available with 4x4 transmission, they can easily cover surfaces of **up to 10,000 m²**.




Technical data

Model	 TONKAWA 110 4x4	 TUAREG 92 EVO	 TUAREG 92 EVO 4X4
Turning radius	73 cm	65 cm	65 cm
Engine make/model	B&S Vanguard V-Twin	Emak K 2400 AVD V-Twin, B&S Vanguard V-Twin	Emak K 2400 AVD V-Twin, B&S Vanguard V-Twin
Cutting height	40-120 mm, 4 positions	50-120 mm, 6 positions	50-120 mm, 6 positions
Mulching/Side discharge	optional/not available	not available/not available	not available/not available
Overall dimensions	235x116x174 cm	231x101x151 cm	231x101x151 cm
Number of blades	3	1	1
Propulsion	4x4 hydrostatic - self-locking differential	hydrostatic, self-locking differential	hydrostatic 4x4, self-locking differential
Displacement	627 cm³	570 cm³ - 708 cm³	627 cm³ - 708 cm³
Weight	401 kg	317 kg	350 kg
Plus	< 10 000 m²	< 9000 m²	< 9000 m²
Speed (km/h)	from 0 to 9.0 km/h in forward drive - from 0 to 5.0 km/h in reverse	from 0 to 8.5 km/h in forward drive - from 0 to 4.5 km/h in reverse	from 0 to 9.0 km/h in forward drive - from 0 to 5.0 km/h in reverse
Cutting width	110 cm	92 cm	92 cm

Compatible accessories


Battery chargers

Efficiency and durability

		Code	EF 86 R/12,5 K M	EF 86 R/14,5 K	TONKAWA 110 4x4	ZEPHYR 72/12,5 K H	ZEPHYR 72/13 H	EF 99 L/12,5 K M	EF 99 L/14,5 K	EF 109 L/16 K	EF 92 R/16 K	EF 95/16 K	EF 102 R/16 K	EF 105/16 K	TUAREG 92 EVO	EF 125/22 V	TUAREG 92 EVO 4X4
	Battery charger	68130481	-	-	X	X	X	X	X	X	-	-	-	-	X	-	X


Trailer

Easy transport of garden waste

		Code	EF 86 R/12,5 K M	EF 86 R/14,5 K	TONKAWA 110 4x4	ZEPHYR 72/12,5 K H	ZEPHYR 72/13 H	EF 99 L/12,5 K M	EF 99 L/14,5 K	EF 109 L/16 K	EF 92 R/16 K	EF 95/16 K	EF 102 R/16 K	EF 105/16 K	TUAREG 92 EVO	EF 125/22 V	TUAREG 92 EVO 4X4
	Trailer	68130005A	-	-	X	X	X	X	X	X	-	-	-	-	X	-	X

Snow chains

Work on the snow without difficulty

		Code	EF 86 R/12,5 K M	EF 86 R/14,5 K	TONKAWA 110 4x4	ZEPHYR 72/12,5 K H	ZEPHYR 72/13 H	EF 99 L/12,5 K M	EF 99 L/14,5 K	EF 109 L/16 K	EF 92 R/16 K	EF 95/16 K	EF 102 R/16 K	EF 105/16 K	TUAREG 92 EVO	EF 125/22 V	TUAREG 92 EVO 4X4
	Snow chains	68050026	-	-	-	-	-	X	X	X	-	-	-	-	-	-	-

Discharge deflector

The key concept: long working times

[illegible]

Mulching kit

The elegance of a perfectly mown lawn

[illegible]

Towing trailer kit

A support to the capabilities of your garden tractor

[illegible]

Snow blade

To remove snow and ice from footpaths


[illegible]

Fuel

[illegible]


Steering wheel knob

For ergonomic manoeuvres using one hand only

	Steering wheel knob	68130600	-	-	-	-	X	-	-	-	-	-	-	-	-	-	-	-	-
		Code	EF 86 R/12,5 K M	EF 86 R/14,5 K	TONKAWA 110 4x4	ZEPHYR 72/12,5 K H	ZEPHYR 72/13 H	EF 99 L/12,5 K M	EF 99 L/14,5 K	EF 109 L/16 K	EF 92 R/16 K	EF 95/16 K	EF 102 R/16 K	EF 105/16 K	TUAREG 92 EVO	EF 125/22 V	TUAREG 92 EVO 4X4		

Lawn roller

For a consistently compact lawn, even after lawncare activities

	Lawn roller	Code	EF 86 R/12,5 K M	EF 86 R/14,5 K	TONKAWA 110 4x4	ZEPHYR 72/12,5 K H	ZEPHYR 72/13 H	EF 99 L/12,5 K M	EF 99 L/14,5 K	EF 109 L/16 K	EF 92 R/16 K	EF 95/16 K	EF 102 R/16 K	EF 105/16 K	TUAREG 92 EVO	EF 125/22 V	TUAREG 92 EVO 4X4
			-	-	X	X	X	X	X	X	-	-	-	-	X	-	X