

TECHNICAL DATA SHEET

Language	ENGLISH
Subject	EUROSINT 2 EVO
	100% synthetic ester based 2-stroke oil



our power, your passion

EUROSINT 2 EVO

EFCO EUROSINT 2 EVO

100% synthetic ester based 2-stroke oil, for highly stressed engines in gardening equipment.

<p>Description</p> <p>Exclusively developed for highly stressed 2-stroke engines, based on synthetic esters with outstanding lubricating and anti-wear properties.</p> <p>The product can be easily mixed with all kind of fuels, no matter the outside temperature.</p> <p>Its specific additive package allows the fuel-oil mixture to remain stable even if not used, for long periods</p> <p>Specifications</p> <ul style="list-style-type: none">• API TC• JASO FD• ISO-L-EGD	<p>Benefits</p> <ul style="list-style-type: none">• 100% synthetic ester.• Exceptional performance and superior engine protection.• Very high load resistance.
----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Average Typical Data

Properties	Unit	Value	Test Method
SAE Grade		40	
Colour		Blue	
Density @ 20°C	Kg/l	0.920	ASTM D 1298
Viscosity @ 40°C	mm ² /s	98.60	ASTM D 445
Viscosity @ 100°C	mm ² /s	13.50	ASTM D 445
Viscosity Index		137	ASTM D 2270

Application

Suitable for all high performance 2-stroke, air-cooled and water-cooled engines of gardening equipment, chainsaws, lawnmowers, etc.

It can be used both with normal and unleaded petrol.

Mixture from 2 to 3% are accepted, as specified by the manufacturer.

Also suitable for competition 2-stroke engines (motorcycles, karts ...).



It's an **Emak S.p.A.** trademark
42011 Bagnolo in Piano (RE) Italy
🌐 www.efco.com
▶ www.youtube.com/MyEfco
📘 www.facebook.com/Efcoltalia
📷 www.instagram.com/Efcoltalia