



It's an Emak S.p.A. trademark
42011 Bagnolo in Piano (RE) Italy
Tel. +39 0522 956611 • Fax +39 0522 951555
info@myefco.com • www.myefco.com
YouTube www.youtube.com/MyEfco

3085494

NEW CHAINSAW MTT 2500



PERFORMANCE
DESIGN
COMFORT



PERFORMANCE



HIGH CUTTING TORQUE

DESIGN



NEW, MORE ERGONOMIC DESIGN



COMFORT



LIGHTWEIGHT AND BALANCED, ALWAYS

NYLON AIR FILTER
Large size filter element for more efficient air intake and reduced maintenance times

ON-BOARD CLUTCH
Quick fitting of bar and chain, cleaner clutch for lasting performance

SNAP HOOK
Fold away steel snap hook designed for rapid attachment of the tool to the operator's harness

ALUMINIUM OILER
Optimal lubrication of bar and chain, even in tough working conditions

PROFESSIONAL ENGINE

- Light alloy crankcase
- Nickel plated cylinder
- Two-ring piston
- Two-part forged crankshaft

TRANSLUCENT TANKS
Oil and fuel levels can be monitored easily thus reducing unscheduled stops for top-ups

"EASY ON" FACILITATED STARTING
Reduces the compression effect of the professional engine for effortless starts

"ALWAYS-ON" SWITCH
Fast stopping and always ready to restart thanks to the spring return function

AIR PURGE
Assists cold starts and starting after refuelling

CLEAN CUTS IN ALL CONDITIONS
Acceleration and torque when needed for high cutting quality and minimum operator fatigue

TECHNICAL SPECIFICATIONS

POWER/DISPLACEMENT	1.3 HP - 1.0 kW/25.4 cm ³
BAR LENGTH (nose)	25 cm/10" (sprocket/carving tip)
CHAIN (pitch x gauge)	3/8" x .050" (sprocket) 1/4" x .050" (sprocket) 1/4" x .050" (carving tip)
CHAIN TENSION ADJUSTER	lateral
OILER	aluminium, automatic /zero flow rate at idle speed
OIL RESERVOIR / FUEL TANK CAPACITY	0.16 l/0.23 l
TANK FILLER NECK	Ø 28 (fuel) / Ø 24 (oil)
CLUTCH	On-Board
ON-OFF SYSTEM	Always-On
DRY WEIGHT WITHOUT BAR AND CHAIN	2.7 Kg

PROTECTIVE CLOTHING

Professional protective helmet with integral face shield and noise filtering ear defenders

Jacket with anti-cut protection, resistant to chain speeds of up to 20 m/sec

Tree climbing trousers with anti-cut protection, resistant to chain speeds of up to 20 m/sec

Anti-cut forestry boots with reinforced toecap, resistant to chain speeds of up to 24 m/sec

For sound advice, just ask our authorized dealer.