

ALL-TERRAIN TUAREG 85 2WD

Robust and reliable, these brush-cutting tractors are designed for maintaining large areas of up to 7,000 m². Ideal for clearing overgrown land, rough terrain and slopes where grass collection is not required, they combine high performance with ease of use.

To enhance operator comfort and efficiency, they feature a hydrostatic transmission with lever-controlled speed and direction, an automatic limited-slip differential and electromagnetic blade engagement. Cruise control is standard across the range, allowing a constant working speed to be maintained with ease.



All-terrain TUAREG 85

Low centre of gravity engine and seat for enhanced stability and safety
Front-mounted fuel tank for improved weight distribution and reduced heat exposure
Steel footplate with anti-slip embossing for secure footing in all working conditions
Side handles for additional support when operating on slopes
Integrated cup holder and storage compartment

All-terrain TUAREG 85

- Low centre of gravity engine and seat for enhanced stability and safety
- Front-mounted fuel tank for improved weight distribution and reduced heat exposure
- Steel footplate with anti-slip embossing for secure footing in all working conditions
- Side handles for additional support when operating on slopes
- Integrated cup holder and storage compartment



Plus point



Limited-slip differential

Improves traction on slopes and challenging terrain, providing greater stability and control during operation.



V-twin engine


The high torque of the V-twin engine delivers consistent power and reliable performance, even under demanding working conditions.




Mower deck design

The deck's optimized geometry promotes finer grass mulching, improving cutting quality and delivering a cleaner, more uniform finish.

Technical data

Model	 TUAREG 85 2WD
Displacement	452 cm ³ - 635 cm ³
Cutting width	85 cm
Number of blades	1 (with 2 floating blades)
Engine make/model	Emak K 1600 AVD - Emak K 2000 AVD V-Twin
Cutting height	35-85 mm, 5 positions
Propulsion	hydrostatic, self-locking differential
Speed (km/h)	from 0 to 8.5 km/h in forward drive - from 0 to 4.5 km/h in reverse
Turning radius	78 cm
Overall dimensions	194×93×100 cm
Plus	< 7000 m ²
Mulching/Side discharge	optional/optional
Weight	232 kg

Fuel

		Code	TUAREG 85 2WD
	Petrol jerry can 5 l	4175169A	X